



Collect A versatile outdoor mat

Also available with Pura Backing™

| | | | |
|----------|---------|---------|------------|
| Type | Use | Traffic | Mat Matrix |
| Scraping | Outdoor | High | E |



Collect is a hardwearing outdoor mat that excels at picking up dirt in the entrance areas of commercial buildings and medium-sized and large offices.

Design

Collect has a tough, coarse, loop pile. In combination with scraper fibres in two colours, these loops give Collect a textured surface. The functional yarns feel hard and raw. Three practical colours are available. The red tone draws attention to the entrance area, while the neutral, more serviceable grey blends seamlessly into the background. The full, dark-brown, earth tone fits perfectly with warm interiors.


Matching all floors

Our designers develop colourways that complement every interior style. For ambiances ranging from classic to modern design. The broad Rinos range always has the right solution, to complement both interior design and floor type. **Make your own combination on our website and be inspired by our options.**



Pavement medium gray with **Collect anthracite**

Colours



Anthracite
007
NCS: 8500N



Brown
014
NCS: 8502R



Red
016
NCS: 3560R




Specifications

PVC

PURA[®] BACKING

| | | |
|--------------------------------------|---------------------------------|---------------------------------|
| Pile material | 100% Polyamide | 100% Polyamide |
| Pile weight ISO 8543 | ± 600 gram/m ² | ± 600 gram/m ² |
| Use classification EN 1307 | 33 | 33 |
| Flammability Euroclass EN 13501 | Cfl /s1 | Cfl /s1 |
| Sizes rolls *** | 100/200 cm, ± 20 m ¹ | 100/200 cm, ± 20 m ¹ |
| Sizes mats*** | 60/90, 90/150 cm | 60/90, 90/150 cm |
| Backing | PVC | PU |
| Sand absorption class* | 2 | 2 |
| Optical Class** | NPD | NPD |
| Absorption capacity TNO W6034 | ± 3,8 l/m ² | ± 3,8 l/m ² |
| Total weight ISO 8543 | ± 3.000 g/m ² | ± 2.700 g/m² |
| Pile height ISO 1766 | ± 6,5 mm | ± 6,5 mm |
| Total height ISO 1765 | ± 8,0 mm | ± 8,0 mm |
| Pile density ISO 8543 | 0,079 g/cm ² | 0,079 g/cm ² |
| Number of stitches ISO 1763 | ± 64.500 /m ² | ± 64.500 /m ² |
| Wearing class EN 1963 | 33 | 33 |
| Comfort EN 1307 | LC1 | LC1 |
| Dimensional stability ISO 2551 | <0,4% | <0,4% |
| Light fastness ISO 105 B02 | >7 | >7 |
| Water fastness ISO 105 B01 | 4 – 5 | 4 – 5 |
| Rubbing fastness ISO 105 X12 | 4 – 5 | 4 – 5 |
| Salt water ISO 105 E02 | 4 – 5 | 4 – 5 |
| Shampoo BS 1006 | 4 – 5 | 4 – 5 |
| Organic solvents ISO 105 X05 | 4 – 5 | 4 – 5 |
| Static charge ISO 6356 | <0,1 kV | <0,1 kV |
| Slip Resistance EN 13893 | DS | DS |
| Yarn construction | Bouclé | Bouclé |
| Design | Blended | Blended |
| Colours | 3 | 3 |
| Suitability for stairs EN 1963 | Intensive use | Intensive use |
| Suitability for castor chairs EN 985 | Intensive use | Intensive use |
| Primary backing | nonwoven PET/PA | nonwoven PET/PA |
| Declaration of Performance | Available | Available |

 Excluding loose-laid mats
EN 14061:2004

* Sand Absorption Class 3: ≥90%, Sand Absorption Class 2: 80% = class 2 < 90%, Sand Absorption Class 1: = < 80% ** Optical Class: 5 is best, 1 is lowest *** All listed dimensions include a PVC edge of 2.5 cm. The roll lengths are an indication. Delivered length can be up to 15% higher or lower. Installation and maintenance advice is available on our website.

PURA[®] BACKING

Pura Backing™ makes walk-off entrance mats more sustainable by avoiding the use of PVC and plasticisers. It's the response to increasing demand by commercial and residential decorators for environmental sensitivity and sustainability, down to the last details – even when it comes to entrance mats. Mats with Pura Backing™ meet this requirement – with zero PVC and plasticiser content and a smaller environmental footprint, while being even easier to install!

Contact us for more information

Our employees are ready to answer questions or to take your orders. **Call +31 38 385 35 00** or mail customerservice@rinos.com

Where to use?

| | high traffic | medium traffic |
|--|--------------|----------------|
| Not combined with outdoor matting (scraping) | A | B |
| Combined with outdoor matting (absorbing) | C | D |
| Outdoor matting | E | |

© Rinos B.V.

rinos.com/products/collect