

Gibson

The champion at sand absorption

Also available with Pura Backing™

Type	Use	Traffic	Mat Matrix
Scraping	Indoor	High	A

Gibson is a superior entrance mat when it comes to capturing sand and absorbing moisture in the high-traffic areas of large and medium sized buildings. The sand, dirt and moisture walked in by countless pairs of feet is left behind on the Gibson. Highly recommended in situations without an outdoor mat.

Of all our scraper walk-off entrance mats, Gibson has the highest classification for sand absorption (3). Gibson can also absorb as much as six litres of water per square metre. How? Through a combination of velour absorption segments and linear scraper segments. The scraper segments catch the sand, while the velour absorbs all the moisture.

Gibson is an extremely wear-resistant, walk-off entrance carpet, also under conditions of intensive foot traffic (use class 33). The mat is available in seven colours and with optional Pura Backing – the environmentally friendly and easier to install alternative to PVC.

Design

Gibson alternates unicoloured and grey-black melange lines in a fine, line pattern. It combines soft velour yarn with a hard, scraper fibre. The bright-red colour scheme clearly indicates the location of an entrance. In addition to cool greys and browns, there is also a bright, business-like blue in the colour palette.



Ceramics – natural stones tile warm beige with Gibson blue

Matching all floors

Our designers develop colourways that complement every interior style. For ambiances ranging from classic to modern design. The broad Rinos range always has the right solution, to complement both interior design and floor type. **Make your own combination on our website and be inspired by our options.**


Colours



Black
150
NCS: 9000N



Beige
151
NCS: 5005Y80R



Brown
152
NCS: 8508Y80R




Taupe
154
NCS: 8000N



Grey
155
NCS: 8502B



Blue
156
NCS: 7020R90B



Red
159
NCS: 1580R

Specifications

PVC

PURA[®] BACKING

Pile material	100% Polyamide	100% Polyamide
Pile weight ISO 8543	± 700 g/m ²	± 700 g/m ²
Use classification EN 1307	33	33
Flammability Euroclass EN 13501	Cfl/s1	Cfl/s1
Sizes rolls ***	135/200 cm, ± 20 m ¹	135/200 cm, ± 20 m ¹
Sizes mats***	60/90, 90/150, 135/200 cm	60/90, 90/150, 135/200 cm
Backing	PVC	PU
Sand absorption class*	3	3
Optical class**	3,5	3,5
Absorption capacity TNO W6034	± 6,0 l/m ²	± 6,0 l/m ²
Total weight ISO 8543	± 3.100 g/m ²	± 2.900 gram/m²
Pile height ISO 1766	± 6,0 mm	± 6,0 mm
Total height ISO 1765	± 8,0 mm	± 8,0 mm
Pile density ISO 8543	0,09 g/cm ²	0,09 g/cm ²
Number of stitches ISO 1763	± 78.120 /m ²	± 78.120 /m ²
Wearing class EN 1963	33	33
Comfort EN 1307	LC2	LC2
Dimensional stability ISO 2551	<0,4%	<0,4%
Light fastness ISO 105 B02	>7	>7
Water fastness ISO 105 B01	4 – 5	4 – 5
Rubbing fastness ISO 105 X12	4 – 5	4 – 5
Salt water ISO 105 E02	4 – 5	4 – 5
Shampoo BS 1006	4 – 5	4 – 5
Organic solvents ISO 105 X05	4 – 5	4 – 5
Static charge ISO 6356	2,0 kV	2,0 kV
Slip Resistance EN 13893	DS	DS
Yarn construction	Velours	Velours
Design	Linear	Linear
Colours	7	7
Suitability for stairs EN 1963	Intensive use	Intensive use
Suitability for castor chairs EN 985	Intensive use	Intensive use
Primary backing	nonwoven PET/PA	nonwoven PET/PA
Declaration of Performance	Available	Available

 Excluding loose-laid mats
EN 14061:2004

* Sand Absorption Class 3: ≥90%, Sand Absorption Class 2: 80% ≤ class 2 < 90%, Sand Absorption Class 1: ≤ 80% ** Optical Class: 5 is best, 1 is lowest *** All listed dimensions include a PVC edge of 2.5 cm. The roll lengths are an indication. Delivered length can be up to 15% higher or lower. Installation and maintenance advice is available on our website.

PURA[®] BACKING

Pura Backing™ makes walk-off entrance mats more sustainable by avoiding the use of PVC and plasticisers. It's the response to increasing demand by commercial and residential decorators for environmental sensitivity and sustainability, down to the last details – even when it comes to entrance mats. Mats with Pura Backing™ meet this requirement – with zero PVC and plasticiser content and a smaller environmental footprint, while being even easier to install!

Contact us for more information

Our employees are ready to answer questions or to take your orders. **Call +31 38 385 35 00** or mail customerservice@rinos.com

Where to use?

	high traffic	medium traffic
Not combined with outdoor matting (scraping)	A	B
Combined with outdoor matting (absorbing)	C	D
Outdoor matting	E	

© Rinos B.V.

rinos.com/products/gibson