



Hudson Complements any interior

Also available with Pura Backing™

Type	Use	Traffic	Mat Matrix
Absorbent	Indoor	Medium	D



Hudson is a hardwearing and highly absorbent entrance mat with a lightly mottled design for a business-like image in any interior.

Design

Hudson is a compact, low-pile, velour entrance mat with a matt appearance. The variously coloured yarns create a wavy graphic effect. While the subtle white dot ensures that small dirt particles do not stand out. The soft, felt-like texture feels firm. In addition to two business-like greys, there are sand and earth tones, all of which go well with both cool and warm interiors.




Wood dark black with Hudson beige


Matching all floors

Our designers develop colourways that complement every interior style. For ambiances ranging from classic to modern design. The broad Rinos range always has the right solution, to complement both interior design and floor type. **Make your own combination on our website and be inspired by our options.**


Colours




Beige
841
NCS: 6010Y30R




Blue
846
NCS: 6020R80B



Brown
842
NCS: 7010Y70R



Grey
848
NCS: 6500N



Red
849
NCS: 7020R10B



Black
840
NCS: 8500N




Specifications

PVC

PURA[®] BACKING

Pile material	100% Polyamide	100% Polyamide
Pile weight ISO 8543	± 550 gram/m ²	± 550 gram/m ²
Use classification EN 1307	32	32
Flammability Euroclass EN 13501	Cfl /s1	Cfl /s1
Sizes rolls ***	135/200 cm, ± 20 m ¹	135/200 cm, ± 20 m ¹
Sizes mats***	60/90, 90/150, 135/200 cm	60/90, 90/150, 135/200 cm
Backing	PVC	PU
Sand absorption class*	1	1
Absorption capacity TNO W6034	± 4,8 l/m ²	± 4,8 l/m ²
Total weight ISO 8543	± 2.700 gram/m ²	± 2.400 gram/m²
Pile height ISO 1766	± 4,5 mm	± 4,5 mm
Total height ISO 1765	± 6,5 mm	± 6,5 mm
Pile density ISO 8543	0,092 g/cm ²	0,092 g/cm ²
Number of stitches ISO 1763	ca. 91.000 /m ²	ca. 91.000 /m ²
Wearing class EN 1963	32	32
Comfort EN 1307	LC1	LC1
Dimensional stability ISO 2551	<0,3%	<0,3%
Light fastness ISO 105 B02	>7	>7
Water fastness ISO 105 B01	4 – 5	4 – 5
Rubbing fastness ISO 105 X12	4 – 5	4 – 5
Salt water ISO 105 E02	4 – 5	4 – 5
Shampoo BS 1006	4 – 5	4 – 5
Organic solvents ISO 105 X05	4 – 5	4 – 5
Static charge ISO 6356	<-2,0 kV	<-2,0 kV
Slip Resistance EN 13893	DS	DS
Yarn construction	Velours	Velours
Design	Blended	Blended
Colours	6	6
Suitability for stairs EN 1963	Intensive use	Intensive use
Suitability for castor chairs EN 985	Intensive use	Intensive use
Primary backing	nonwoven PET/PA	nonwoven PET/PA
Declaration of Performance	Available	Available

 Excluding loose-laid mats
EN 14061:2004

* Sand Absorption Class 3: ≥90%, Sand Absorption Class 2: 80% ≤ class 2 < 90%, Sand Absorption Class 1: ≤ 80% ** Optical Class: 5 is best, 1 is lowest *** All listed dimensions include a PVC edge of 2.5 cm. The roll lengths are an indication. Delivered length can be up to 15% higher or lower. Installation and maintenance advice is available on our website.

PURA[®] BACKING

Pura Backing™ makes walk-off entrance mats more sustainable by avoiding the use of PVC and plasticisers. It's the response to increasing demand by commercial and residential decorators for environmental sensitivity and sustainability, down to the last details – even when it comes to entrance mats. Mats with Pura Backing™ meet this requirement – with zero PVC and plasticiser content and a smaller environmental footprint, while being even easier to install!

Contact us for more information

Our employees are ready to answer questions or to take your orders. **Call +31 38 385 35 00** or mail customerservice@rinos.com

Where to use?

	high traffic	medium traffic
Not combined with outdoor matting (scraping)	A	B
Combined with outdoor matting (absorbing)	C	D
Outdoor matting	E	

© Rinos B.V.

rinos.com/products/hudson