



Sonata

Let your floor live

Also available with Pura Backing™

ECONYL®

Type	Use	Traffic	Mat Matrix
Scraping	Indoor	Medium	C



Sonata is a scraping walk-off mat that feels at home in environments with up to 500 passages per day. An attractively priced mat, available in the three best-selling colours.

Design

Sonata has a detailed, cut pile. The mat combines a coarse, black scraper fibre with a soft, multi-coloured yarn. This gives a terazzo-like, stone effect. The shades of grey reflect urban environment tones, such as granite, asphalt, pebbles, cement and concrete paving. Sonata connects exterior and interior in buildings with open facades.




Ceramics – natural stones tile dark grey with Sonata traffic Black

Matching all floors

Our designers develop colourways that complement every interior style. For ambiances ranging from classic to modern design. The broad Rinos range always has the right solution, to complement both interior design and floor type.


Colours



Traffic Black
SO51
NCS: 8500N



Black grey
SO82
NCS: 7502G



Chocolate Brown
SO21
NCS: 8005Y50R




Specifications

PVC

PURA^{BACKING}

Pile material	100% recycled (ECONYL®) Polyamide	100% recycled (ECONYL®) Polyamide
Pile weight ISO 8543	500 g/m ²	500 g/m ²
Use classification EN 1307	32	32
Flammability Euroclass EN 13501	Cfl-s1	Cfl-s1
Sizes rolls (w*I) ***	135 cm/ 20 m ¹ , 200 cm/ 20 m ¹	135 cm/20 m ¹ , 200 cm/20 m ¹
Sizes mats (w*I) ***	60*90, 90*150 cm	60*90, 90*150 cm
Sand absorption class*	npd	npd
Optical class**	npd	npd
Absorption capacity TNO W6034	± 3,5 l/m ²	± 3,5 l/m ²
Total weight ISO 8543	ca. 2.900 g/m ²	ca. 2.700 g/m ²
Pile height ISO 1766	ca. 5,0 mm	ca. 5,0 mm
Total height ISO 1765	ca. 7,0 mm	ca. 7,0 mm
Pile density ISO 8543	0,088 g/m ²	0,088 g/m ²
Number of stitches ISO 1763	ca. 67.600 /m ²	ca. 67.600 /m ²
Wearing class EN 1963	32	32
Comfort EN 1307	LC1	LC1
Dimensional stability ISO 2551	< 0,4%	< 0,4%
Impact sound insulation EN 1307 annex D.	≥ 10 dB	≥ 10 dB
Light fastness ISO 105 B02	>6	>6
Water fastness ISO 105 B01	4	4
Rubbing fastness ISO 105 X12	4	4
Salt water ISO 105 E02	4	4
Shampoo BS 1006	4	4
Organic solvents ISO 105 X05	4	4
Static charge ISO 6356	=<2,0 kV	=<2,0 kV
Thermal resistance EN 12667	m ² K/W	m ² K/W
Slip Resistance EN 13893	DS	DS
Yarn construction	cut pile	cut pile
Design	Heathered	Heathered
Colouring	Piece dye	Piece dye
Colours	3	3
Suitability for stairs EN 1963	Incidental use	Incidental use
Suitability for castor chairs EN 985	Incidental use	Incidental use
Backing	PVC	PU
Primary backing	nonwoven PET/PA	nonwoven PET/PA

 Excluding loose-laid mats
EN 18041:2004

*Sand absorption classification Class 3: >=90%, Sand absorption classification: 80% =< class 2 < 90%, Sand absorption classification Class 1: =< 80% **Optical classification: 5 indicates highest, 1 indicates lowest ***All listed width dimensions include a PVC edge of 2,5 cm at both sides. The roll lengths are an indication. Delivered length can be up to 15% higher or lower. Installation and maintenance advice is available at our website.

PURA^{BACKING}

Pura Backing™ is a unique Rinos product innovation, developed by our R&D department. It's the Rinos answer to increasing demand for more environmentally friendly and sustainable entrance mat solutions by avoiding the use of PVC and plasticisers. Mats with Pura Backing™ meet this requirement – with zero PVC and plasticiser content, avoiding stains on porous subfloors. Thanks to increased flexibility, it is even easier to install!

Contact us for more information

Our employees are ready to answer questions or to take your orders. **Call +31 38 385 35 00** or **mail customerservice@rinos.com**

Where to use?

	high traffic	medium traffic
Not combined with outdoor matting (scraping)	A	B
Combined with outdoor matting (absorbing)	C	D
Outdoor matting	E	

© Rinos B.V.

rinos.com/products/sonata