

Nubia

An entrance mat with character

Also available with Pura Backing™

ECONYL®

| Type | Use | Traffic | Mat Matrix |
|----------|--------|---------|------------|
| Scraping | Indoor | Medium | B |



Nubia is a highly sought-after, moisture-absorbing entrance mat with a light scraper fibre, for medium-traffic applications.

Nubia offers value for money. It is a particularly popular entrance mat, with loads of character. This lightly mottled mat is easy to install and extremely functional. The wear-resistant ECONYL® polyamide absorbs moisture and the light scraper fibre prevents dirt being walked in.

Design

Nubia has a soft touch and a low pile. With a woolly, cut pile and a fine scraper fibre. Its robust, no-nonsense appearance is reflected in three, super-functional colours: basic black, medium grey and cool brown.




Wood light oak floor herringbone coarse with Nubia grey

Matching all floors

Our designers develop colourways that complement every interior style. For ambiances ranging from classic to modern design. The broad Rinos range always has the right solution, to complement both interior design and floor type. **Make your own combination on our website and be inspired by our options.**


Colours



Brown
092
NCS: 8005Y80R



Grey
095
NCS: 8502B




Black
090
NCS: 9000N

Specifications

PVC

PURA^{BACKING}

| | | |
|--|--|--|
| Pile material | 100% regenerated ECONYL [®] Polyamide | 100% regenerated ECONYL [®] Polyamide |
| Pile weight ISO 8543 | ca. 600 g/m ² | ca. 600 g/m ² |
| Use classification EN 1307 | 32 | 32 |
| Flammability Euroclass EN 13501 | Cfl-s1 | Cfl-s1 |
| Sizes rolls (w*I) *** | 135 cm/ 20 m ¹ , 200 cm/ 20 m ¹ | 135 cm/ 20 m ¹ , 200 cm/ 20 m ¹ |
| Sizes mats (w*I) *** | | |
| Backing | Phtalate-free PVC | PU |
| Sand absorption class* | 3 | 3 |
| Optical class** | 4 | 4 |
| Absorption capacity TNO W6034 | 4,4 l/m ² | 4,4 l/m ² |
| Total weight ISO 8543 | ca. 2.800 g/m ² | ca. 2.400 g/m ² |
| Pile height ISO 1766 | ca. 5,5 mm | ca. 5,5 mm |
| Total height ISO 1765 | ca. 7,5 mm | ca. 7,5 mm |
| Pile density ISO 8543 | 0,094 g/cm ² | 0,094 g/cm ² |
| Number of stitches ISO 1763 | ca. 64.250 /m ² | ca. 64.250 /m ² |
| Wearing class EN 1963 | 32 | 32 |
| Comfort EN 1307 | LC1 | LC1 |
| Dimensional stability ISO 2551 | <0,4 % | <0,4 % |
| Light fastness ISO 105 B02 | >7 | >7 |
| Water fastness ISO 105 B01 | 4 - 5 | 4 - 5 |
| Rubbing fastness ISO 105 X12 | 4 - 5 | 4 - 5 |
| Salt water ISO 105 E02 | 4 - 5 | 4 - 5 |
| Shampoo BS 1006 | 4 - 5 | 4 - 5 |
| Organic solvents ISO 105 X05 | 4 - 5 | 4 - 5 |
| Static charge ISO 6356 | <2,0 kV | <2,0 kV |
| Slip Resistance EN 13893 | DS | DS |
| Yarn construction | Cut Pile | Cut Pile |
| Design | Heathered | Heathered |
| Colours | 3 | 3 |
| Suitability for stairs EN 1963 | Incidental use | Incidental use |
| Suitability for castor chairs EN 985 | Incidental use | Incidental use |
| Primary backing | nonwoven PET/PA | nonwoven PET/PA |
| Thermal resistance EN 12667 | 0,08 m ² K/W | 0,08 m ² K/W |
| Impact sound insulation EN 1307 annex D. | ≥ 10 dB | ≥ 10 dB |
| Colouring | Solution dyed | Solution dyed |
| Circularity index | 73 % | 60 % |

 Excluding loose-laid mats
EN 14041:2004

* Sand Absorption Class 3: ≥90%, Sand Absorption Class 2: 80% ≤ class 2 < 90%, Sand Absorption Class 1: ≤ 80% ** Optical Class: 5 is best, 1 is lowest *** All listed dimensions include a PVC edge of 2.5 cm. The roll lengths are an indication. Delivered length can be up to 15% higher or lower. Installation and maintenance advice is available on our website.



PURA^{BACKING}

Pura Backing™ makes walk-off entrance mats more sustainable by avoiding the use of PVC and plasticisers. It's the response to increasing demand by commercial and residential decorators for environmental sensitivity and sustainability, down to the last details – even when it comes to entrance mats. Mats with Pura Backing™ meet this requirement – with zero PVC and plasticiser content and a smaller environmental footprint, while being even easier to install!

Contact us for more information

Our employees are ready to answer questions or to take your orders. **Call +31 38 385 35 00** or mail customerservice@rinos.com

Where to use?

| | high traffic | medium traffic |
|---|--------------|----------------|
| Not combined with outdoor matting (scrapping) | A | B |
| Combined with outdoor matting (absorbing) | C | D |
| Outdoor matting | E | |

© Rinos B.V.

rinos.com/products/nubia